

AMENDMENTS TO THE CLAIMS:

The listing of claims will replace all prior versions, and listings of claims in the application:

LISTING OF THE CLAIMS

1. (Original) An electric arc welder for performing a given weld process with a selected A.C. pulse current waveform performed between an electrode and a workpiece, said current waveform including a positive segment and a negative segment, with at least one segment including a peak current and background current, said welder comprising: a power source with a controller having a digital processor including a program to calculate the real time power factor of the weld current and weld voltage, said program including an algorithm to calculate the rms weld voltage, the rms weld current and the average power of said power source; a circuit to multiply said rms current by said rms voltage to produce an rms power level; a circuit to divide said average power by said rms power to create a value representing the actual real time power factor of said power source; and, a circuit to adjust said background current to maintain said power factor at a given level.

2. (Original) An electric arc welder as defined in claim 1 wherein said controller includes a wave shaper having an input with a value determining the shape of said waveform and an error circuit for comparing said actual real time power factor with a desired power factor to create a corrective value and a circuit to direct said value to said input of said wave shaper whereby said actual real time power factor is held at said desired power factor.

3. (Original) An electric arc welder as defined in claim 2 wherein said waveform is created by a number of current pulses occurring at a frequency of at least 18 kHz with a magnitude of each pulse controlled by a wave shaper.

4. (Original) An electric arc welder as defined in claim 1 wherein said waveform is created by a number of current pulses occurring at a frequency of at

least 18 kHz with a magnitude of each pulse controlled by a wave shaper.

5. (Original) An electric arc welder as defined in claim 4 wherein said background current is adjusted in magnitude.

6. (Original) An electric arc welder as defined in claim 4 wherein said background current is adjusted in length.

7. (Original) An electric arc welder as defined in claim 3 wherein said background current is adjusted in magnitude.

8. (Original) An electric arc welder as defined in claim 3 wherein said background current is adjusted in length.

9. (Original) An electric arc welder as defined in claim 2 wherein said background current is adjusted in magnitude.

10. (Original) An electric arc welder as defined in claim 2 wherein said background current is adjusted in length.

11. (Original) An electric arc welder as defined in claim 1 wherein said background current is adjusted in magnitude.

12 (Original) An electric arc welder as defined in claim 1 wherein said background current is adjusted in length.

13. (Original) An electric arc welder as defined in claim 12 including a circuit to control heat of said weld process by adjusting said given level.

14. (Original) An electric arc welder as defined in claim 11 including a circuit to control heat of said weld process by adjusting said given level.

15. (Original) An electric arc welder as defined in claim 6 including a circuit to control heat of said weld process by adjusting said given level.

16. (Original) An electric arc welder as defined in claim 5 including a circuit to control heat of said weld process by adjusting said given level.

17. (Original) An electric arc welder as defined in claim 2 including a circuit to control heat of said weld process by adjusting said given level.

18. (Original) An electric arc welder as defined in claim 1 including a circuit to control heat of said weld process by adjusting said given level.

19. (Original) An electric arc welder for performing a given weld process with a selected A.C. pulse current waveform performed between an electrode and a workpiece, said current waveform including a positive segment and a negative segment, with at least one segment including a peak current and background current, said welder comprising: a power source with a controller having a digital processor including a program to calculate the real time power factor of the weld current and weld voltage, said program including an algorithm to calculate the rms weld voltage, the rms weld current and the average power of said power source; a circuit to multiply said rms

current by said rms voltage to produce an rms power level; a circuit to divide said average power by said rms power to create a value representing the actual real time power factor of said power source; and, a circuit to adjust said peak current to maintain said power factor at a given level.

20. (Original) An electric arc welder as defined in claim 19 wherein said controller includes a wave shaper having an input with a value determining the shape of said waveform and an error circuit for comparing said actual real time power factor with a desired power factor to create a corrective value

and a circuit to direct said value to said input of said wave shaper whereby said actual real time power factor is held at said desired power factor.

21. (Original) An electric arc welder as defined in claim 20 wherein said waveform is created by a number of current pulses occurring at a frequency of at least 18 kHz with a magnitude of each pulse controlled by a wave shaper.

22. (Original) An electric arc welder as defined in claim 19 wherein said waveform is created by a number of current pulses occurring at a frequency of at least 18 kHz with a magnitude of each pulse controlled by a wave shaper.

23. (Original) An electric arc welder as defined in claim 22 wherein said peak current is adjusted in magnitude.

24. (Original) An electric arc welder as defined in claim 22 wherein said peak current is adjusted in length.

25. (Original) An electric arc welder as defined in claim 21 wherein said peak current is adjusted in magnitude.

26. (Original) An electric arc welder as defined in claim 21 wherein said peak current is adjusted in length.

27. (Original) An electric arc welder as defined in claim 20 wherein said peak current is adjusted in magnitude.

28. (Original) An electric arc welder as defined in claim 20 wherein said peak current is adjusted in length.

29. (Original) An electric arc welder as defined in claim 19 wherein said peak current is adjusted in magnitude.

30. (Original) An electric arc welder as defined in claim 19 wherein said peak current is adjusted in length.

31. (Original) An electric arc welder as defined in claim 30 including a circuit to control heat of said weld process by adjusting said given level.

32. (Original) An electric arc welder as defined in claim 24 including a circuit to control heat of said weld process by adjusting said given level.

33. (Original) An electric arc welder as defined in claim 23 including

a circuit to control heat of said weld process by adjusting said given level.

34. (Original) An electric arc welder as defined in claim 20 including a circuit to control heat of said weld process by adjusting said given level.

35. (Original) An electric arc welder as defined in claim 19 including a circuit to control heat of said weld process by adjusting said given level.

36. (Original) An electric arc welder for performing a pulse welding process with a selected waveform performed between an electrode and workpiece, said waveform having a peak current and a background current, said welder comprising: a power source with a waveform generator having a control signal input with a value determining the shape of said waveform; a controller with a comparator program with a first input representative of the actual power factor of said power source, a second input representing a desired power factor and an output signal directed to said control input of said wave shape generator wherein said actual power factor is held at said desired power factor by adjusting said background current of said waveform.

37. (Original) An electric arc welder as defined in claim 36 including a device to manually adjust said desired power factor for adjusting the heat of said weld process.

38. (Original) An electric arc welder as defined in claim 37 including a control circuit for holding the rms current of said power source at a desired set value as said heat is adjusted.

39. (Original) A method of controlling an electric arc welder for

performing a given pulse weld process with a selected waveform performed by a power source between an electrode and workpiece, said waveform having a peak current and a background current, said method comprising:

- (a) calculating the actual power factor of said power source using the rms current and rms voltage;
- (b) selecting a desired power factor for said power source;
- (c) obtaining an error signal by comparing said actual power factor of power source to said desired power factor of the power source; and,
- (d) adjusting background current of said waveform by said error signal whereby said actual power factor is maintained at said desired power factor.

40. (Original) The method as defined in claim 39 including manually adjusting said desired power factor to control the heat of said weld process.

41. (Original) A method as defined in claim 40 including holding said rms current constant as said desired power factor is adjusted.

42. (Original) A method as defined in claim 41 wherein said waveform is created by a number of current pulses occurring at a frequency of at least 18 kHz with a magnitude of each pulse controlled by a wave shaper.

43. (Original) A method as defined in claim 40 wherein said waveform is created by a number of current pulses occurring at a frequency of at least 18 kHz with a magnitude of each pulse controlled by a wave shaper.

44. (Original) A method as defined in claim 39 wherein said

waveform is created by a number of current pulses occurring at a frequency of at least 18 kHz with a magnitude of each pulse controlled by a wave shaper.

45. (Original) An electric arc welder for performing a pulse welding process with a selected waveform performed between an electrode and workpiece, said waveform having a peak current and a background current, said welder comprising: a power source with a waveform generator having a control signal input with a value determining the shape of said waveform; a controller with a comparator program with a first input representative of the actual power factor of said power source, a second input representing a desired power factor and an output signal directed to said control input of said wave shape generator wherein said actual power factor is held at said desired power factor by adjusting said peak current of said waveform.

46. (Original) An electric arc welder as defined in claim 45 including a device to manually adjust said desired power factor for adjusting the heat of said weld process.

47. (Original) An electric arc welder as defined in claim 46 including a control circuit for holding the rms current of said power source at a desired set value as said heat is adjusted.

48. (Original) A method of controlling an electric arc welder for performing a given pulse weld process with a selected waveform performed by a power source between an electrode and workpiece, said waveform having a peak current and a background current, said method comprising:

(a) calculating the actual power factor of said power source using the rms current and rms voltage;

(b) selecting a desired power factor for said power source;

(c) obtaining an error signal by comparing said actual power factor of power source to said desired power factor of the power source; and,

(d) adjusting peak current of said waveform by said error signal whereby said actual power factor is maintained at said desired power factor.

49. (Currently Amended) ~~The A~~ method as defined in claim 48 including manually adjusting said desired power factor to control the heat of said weld process.

50. (Original) A method as defined in claim 49 including holding said rms current constant as said desired power factor is adjusted.

51. (Original) A method as defined in claim 50 wherein said waveform is created by a number of current pulses occurring at a frequency of at least 18 kHz with a magnitude of each pulse controlled by a wave shaper.

52. (Original) A method as defined in claim 49 wherein said waveform is created by a number of current pulses occurring at a frequency of at least 18 kHz with a magnitude of each pulse controlled by a wave shaper.

53. (Original) A method as defined in claim 48 wherein said waveform is created by a number of current pulses occurring at a frequency of at least 18 kHz with a magnitude of each pulse controlled by a wave shaper.

54-91 (Canceled)